



# License Plate Relocation Kit Installation Instructions

For '02-'06 Mini

PART # 102-500

**MOSS MOTORS, LTD.**

440 Rutherford St. P.O. Box 847 Goleta, CA 93117  
1-800-667-7872 • FAX 805-692-2525 • www.mossmotors.com

Tools required: 13mm & 17mm combination wrenches, 17mm socket, 5/32" Allen wrench, scissors, torque wrench

1. Remove the tow hook cover from the passenger side grille. Apply the supplied thread locker to the larger threads on the mounting stud. Install the stud in the tow hook mount and tighten it with a 13mm combination wrench. Illustration 1.



Illustration 1



Illustration 1 con't

2. The top of the license plate bracket is cut out between the treaded holes. Choose which hole you will use to mount the license bracket. Position the bracket level with the bumper. Use a 17mm combination wrench to tighten the lock nut while holding the bracket level. Torque to 34 ft. lbs. Illustration 2.



Illustration 2

## License Plate Relocation Kit Installation Instructions

---

3. The kit supplies four 1/4"-28 screws to secure the license plate to the bracket. If your license plate frame only allows the use of two screws, use the provided double sided tape to keep the license plate from rattling against the bracket. Use scissors to cut the tape. Apply the tape to the legs of the bracket that will not secure the license plate with screws. The tape is supplied only to keep the license plate from rattling against the bracket, not for structural support. Apply thread locker to the 1/4"-28 screws. Install the license plate to the bracket using a 5/32" Allen wrench and at least two of the supplied 1/4"-28 screws. Toque to 5 ft. lbs. Illustration 3.



**Illustration 3**



Enjoy your license plate relocation kit!