



INSTALLATION INSTRUCTIONS

Part Number 33-2034

This filter fits: See current K&N catalog for complete listing

FREE K&N DECAL** To register your warranty, please see us online at knfilters.com/register. **FREE K&N DECAL

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter can last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modifications will be required.

The filter must be installed into the lid of the airbox first, this may require that the intake hose that runs from the airbox to the engine, be removed. Make sure to seat the filter properly into the groove of the lid, the fit will be snug, but this assures an airtight seal. The lid/filter assembly may now be positioned on the airbox. Make sure that the lid is even all the way around, and is not cocked or hanging up. Install the holddown screws, tighten in a criss-cross pattern a little bit at a time until all are snug. The intake hose may now be reinstalled if necessary.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.

• 1455 CITRUS AVE., P.O. BOX 1329, RIVERSIDE, CA., U.S.A. 92502 • TECH SERVICE 800-858-3333 • FAX 909-684-9060
• e-mail: tech@knfilters.com • WWW: <http://www.knfilters.com>

17747



INSTALLATION INSTRUCTIONS

Part Number 33-2034

This filter fits: See current K&N catalog for complete listing

FREE K&N DECAL** To register your warranty, please see us online at knfilters.com/register. **FREE K&N DECAL

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter can last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modifications will be required.

The filter must be installed into the lid of the airbox first, this may require that the intake hose that runs from the airbox to the engine, be removed. Make sure to seat the filter properly into the groove of the lid, the fit will be snug, but this assures an airtight seal. The lid/filter assembly may now be positioned on the airbox. Make sure that the lid is even all the way around, and is not cocked or hanging up. Install the holddown screws, tighten in a criss-cross pattern a little bit at a time until all are snug. The intake hose may now be reinstalled if necessary.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.

• 1455 CITRUS AVE., P.O. BOX 1329, RIVERSIDE, CA., U.S.A. 92502 • TECH SERVICE 800-858-3333 • FAX 909-684-9060
• e-mail: tech@knfilters.com • WWW: <http://www.knfilters.com>

17747